



Altavoces LF - 21.0 Inches







- 94,5 dB SPL 1W / 1m average sensitivity
- 135 mm (5.3 in) split winding four layers ISV copper coil
- 3600 W program power handling
- Carbon fiber cone
- Triple Silicon Spider (TSS) improves excursion control and linearity even in extreme loading and SPL conditions
- Single Demodulating Ring (SDR) for lower distortion
- Low noise cooling design for very low power compression
- Suitable for bandpass and horn loaded subwoofer designs



21NLW9601C 4Ω

Altavoces LF - 21.0 Inches

The 21NLW9601C is a 21 inch neodymium high performance transducer. It is the evolution of the 21NLW9601 speaker. The transducer is suitable for high loading, ultra-low frequency horn loaded as well as bandpass subwoofer designs. For optimum results recommended amplifier should be able to deliver 3600 Watt program power without clipping. At the heart of the transducers stands the improved Triple Silicon Spider (TSS) lets the 21NLW9601C being able to control the moving mass with exceptional linearity, showing an exceptional stability of mechanical parameter values in the long term. The transducer design features include a high performance large displacement suspension system for improved cone control even at very high level of SPL matching. The state-of-the-art 5,3" diameter ISV copper voice coil shows a inside-outside split winding, four layers design, enabling the 21NLW9601C to handle up to 3600W program power. BI force factor as well as all electro-dynamic parameters are linear within the working range. This, together with the high excursion behavior - 70 mm before damage, ±14 mm linear Xmax - makes the 21NLW9601C an extremely low distortion, highly dynamic transducer. The already low distortion and sound quality are further improved by an aluminum Single Demodulating Ring (SDR technology) that flatten impedance and phase with a constant power transfer. The 21NLW9601C has been developed after intense FEA and fluidodynamics simulation and testing, focusing on dissipating the heat generated by the powerful 5.3" coil. Special attention was given to the optimization of air flow into the gap without introducing audible noise. A special low density material air diffractor placed into the backplate acts as a cooling system, increasing the power handling capability and lowering the power compression figure. Weight reduction was a key development aspect of the 21NLW9601C, resulting in a net value of 14kg (30,9b). The carbon fiber cone shows extreme strength and water repellent properties. A special coating applied to both the top and back plates makes the transducer far more resistant to the corrosive effects of salts and oxidization.







21NLW9601C 4Ω

Altavoces LF - 21.0 Inches

ESPECIFICACIÓN

Diámetro nominal	533 mm (in)
Impedancia nominal	4 Ω
Impedancia minima	4.0 Ω
Manejo de potencia nominal	1800 W
Manejo de potencia continua	3600 W
Sensibilidad	94.5 dB
Rango de frecuencia	33 - 2000 Hz
Diámetro de la bobina	135 mm (5.3 in)

PARÁMETROS

Frecuencia de resonancia	38 Hz
Re	2.9 Ω
Qes	0.31
Qms	6.28
Qts	0.29
Vas	140.0 dm ³ (ft ³)
Sd	1662.0 cm ² (257.61 in ²)
Xmax	0.0 mm
Mms	484.0 g
BI	33.2 Txm
Le	1.61 mH
EBP	122 Hz

INFORMACIÓN DE MONTAJE Y ENVÍO

Diámetro total	545 mm (ir	(ו
Diámetro de circunferencia de los to	rnillos	
	520 mm (ir	(ו
Diámetro de la perforación en el baf	fle	
	492.0 mm (ir	ו)
Profundidad	250 mm (ir	(ו
Espesor del reborde y junta	18 mm (ir	(ו
Peso neto	13.6 kg (lk	ว)
Peso del envío	15.1 kg (lk	ว)
Caja de envío		
570x570x290 mm (22,4x22,4x1	1,4 in) mm (ir	۱)